



Maad AF

Thickness:	5,7,10,15,20,25,30,40,50 mm
Colour:	black
Cell structure:	open
Base material:	POLIURETAN -poliester
Width:	1000 mm

		S30P10R	S30P20R	S30P30R	S30P45R	S30P60R	S30P80R
		PPI 10	PPI 20	PPI 30	PPI 44	PPI 60	PPI 80
DENSITY							
DIN EN ISO 845	kg/m ³	28±3	28±3	28±3	28±3	28±3	33±3
HARDNESS CV40							
DIN EN ISO 3386-1	k/Pa	4,0±0,8	3,5±0,8	3,0±0,6	4,5±0,9	4,5±0,9	3,6±0,5
STRENGTH							
DIN 53571	kPa	min. 60	min. 80	min. 100	min. 100	min. 100	min. 100
EXTENSION							
DIN 53571	%	min. 100	min. 120	min. 150	min. 150	min. 150	min. 200
NUMBER OF CELLS	1/cm	2,0-3,2	3,3-5,2	5,5-7,5	10,5-13,5	18±2,0	24,0±2,0
AIR FLOW							
DIN EN ISO 9237	1/m ² *s	6500±1000	5000±1000	3750±750	3000±750	2100±500	1200±500

In the case of material with a self-adhesive layer, storage at a temperature of +15 to +30 °C