





# E20\*118R03/01\*004034\*00

## TYPE - APPROVAL CERTIFICATE MAAD SNK FORM



#### Descripton

MAAD SNK FORM a thermoplastic heavy film made from unvulcanised synthetic rubber (e.g. ethylene - acetate of vinyl - copolymer).

MAAD SNK FORM has an approval certificate issued by Transport Technical Supervision TDT. The material is registered in an international database IMDS. MAAD SNK FROM is easy to shape and has the relatively large mass per unit of surface area. Heat treatment applied during the formation increases the flexibility of the material. Plastoform is produced in the form of boards of different sizes. It does not corrode and is easy to proces during the assembly. When combined with the foils this product meets the highest requirements for acoustic insulation.

#### Application



















	100
-	90 ± 5
-	3,0 – 18,0 kg/ m <sup>2</sup>
-	2,4 ± 0,2 g/cm³
DIN 53504	≥ 2000 kPa
DIN 53504	≥ 30%
ASTM D624-81	≥ 250 N/cm
DIN 53521	unilateral action 4h
-	ok. 0,2 g
Euro-Norma	ok. 7,0 g
-	ok. 0,5 g
PM-B-031X	max 80°C
PM-B-030D	max 150°C
PM-B014X	-30°C (without spatter)
Sound absorption according Rw ISO 717-1	25 dB (A) for 5 kg/m² 29 dB (A) for 8 kg/m² 32 dB (A) for 12 kg/m²
EN 45545-2+A1 DIN 4102 FMVSS 302 DIN 75200 DIN 5510	fulfilled the recommendations R10 - HL 1, HL 2, HL 3 fulfilled the recommendations B2 fulfilled fulfilled fulfilled fulfilled the recommendations S4, ST2, SR2
	DIN 53504 ASTM D624-81 DIN 53521 - Euro-Norma - PM-B-031X PM-B-030D PM-B014X Sound absorption according Rw ISO 717-1  EN 45545-2+A1 DIN 4102 FMVSS 302 DIN 75200

### STANDARD DIMENSIONS OF THE MATERIA

THICKNESS [mm]	DIMENSIONS OF THE SHEET * [mm]
1,25 – 6,0	2000 x 1000

There is a possibility of cutting to size in accordance with your specifications or drawing.

\*Other thicknesses / dimensions available on customer's request. Effective dimensions guaranteed as ordered

OPTIONS**	
Maad SNK Form	

without a self-adhesive layer

Maad SNK Form, SK-M

with a self-adhesive with a mesh layer

<sup>\*\*</sup> Other composites available on customer's request.

